KD9150H

16.2" 1920 x 1200 widescreen LCD monitor with VGA + DVI-D + HDMI video input and 104-key keyboard with touchpad in a 1U high 18.9" depth rackmount drawer.



- 16.2" WUXGA rack LCD console drawer
- Supports 1920 x 1200 native resolution
- VGA + DVI-D + HDMI 1.4 video input
- 104-key keyboard with touchpad or trackball
- Option for Resistive or Projected Capacitive touchscreen
- Audio input and option for front USB hub, 3G-SDI input
- Short-depth drawer design of 18.9" (480mm)
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V DC power input

Description

The KD9150H is a 16.2" WUXGA LCD rack console supporting 1920 x 1200 resolution, a 104-key keyboard with a 2-button touchpad, and 100/240VAC power input. The console features VGA + DVI-D + HDMI 1.4 video input, providing users with multiple options for connecting their devices. The KD9150H is integrated into a 1U rack enclosure that is designed for a standard 19" rack mount space for data centers and other IT environments

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 16.2 inch Native Resolution: 1920 x 1200 Brightness (cd/m²): 300 Contrast Ratio (typ.): 800:1 Viewing Angle (H/V): 178° x 178° Response Time (ms): 30 Dot Pitch (mm): 0.191 Display Area (mm): 343.8H x 214.9V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight Type: LED MTBF (hrs): 20,000

Specifications subject to change without notice.

Keyboard & Pointing Device	104-key keyboard with 2-button touchpad - USB Option for keyboard with trackball or SUN keyboard
Video Input	VGA + DVI-D + HDMI Option for front USB hub, Audio, or 3G-SDI input
Touch Screen (Option)	Resistive 1-pt touch screen - USB port Projected Capacitive 10-pt touch screen - USB port
Front panel control	Power on/off switch OSD (on screen display)
Mounting Distance	19.3~28.3 inch (490~720 mm)
Cable	1 x 6ft DVI-D USB console cable included
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 34W, Standby 4W Option for 12V / 24V / 48V / 125V DC power input
Color	Black (RAL 9005)
Weight	24 lb / 10.9 kg
Dimension	17.4"(W) x 18.9"(D) x 1.73”(H) * All dimensions stated are subject to change if options are selected / integrated to base model
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	FCC, CE, RoHS, TAA Compliant

Available Configurations

Input device

- Touch pad for LCD console drawer
- Trackball for LCD console drawer
- SUN K/B for LCD console drawer

Video input

- VGA + DVI-D + HDMI + Speaker
- Audio + VGA + DVI-D + HDMI + Speaker
- 3G-SDI + VGA + HDMI + Speaker
- Front USB hub + VGA + DVI-D + HDMI + Speaker

Touch Screen

- N/A
- Resistive touch screen, 1-pt
- Projected Capacitive touch screen,10-pt

power input

- 110/220VAC power

Specifications subject to change without notice.

- 12V DC power
- 24V DC power
- 48V DC power
- 125V DC power

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.