KDN9172

1U 17" rack LCD console drawer with 1280 x 1024 resolution, VGA video input, and a 104-key keyboard with a wired mini optical USB mouse in a 1U high 25.6" depth rack chassis.



- 1U 17" rackmount LCD console drawer
- Supports 1280 x 1024 resolution
- 104-key keyboard with a wired mini USB optical mouse
- VGA video input
- Front OSD (On Screen Display) function
- Slim 1U design with front handle and 2-point lock
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V DC power input
- Option 8 or 16 port KVM switch

Description

The KDN9172 is a 17" LCD rack console drawer with 1280 x 1024 resolution, 104-key keyboard with a wired mini USB optical mouse, and VGA video input. Desgiend for standard racks, it allows you to mount this console in 25.60 inches (650mm) of space for data centers and other IT environments. Options are available for DC power input.

Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel
LCD Panel	Size: 17 inch Resolution: 1280 x 1024 Brightness (cd/m²): 250 Contrast Ratio (typ): 1000:1 Viewing Area (mm): 337.92H x 270.33V Viewing Angle (H/V): 170° x 160° Colors: 16.7 M Surface Hardness: 3H Backlight: LED MTBF (hrs): 30,000
Keyboard & Optical mouse	104-key keyboard with a wired mini USB optical mouse
Video Input	VGA video input

Specifications subject to change without notice.

Cable	1 x 6ft VGA console cable included
Mounting Distance	26 ~ 34.3 inch (660 ~ 870 mm)
Power supply	110/220VAC power input - option for 12/24/28/125V DC power input
KVM switch	Option for 8 or 16 port KVM switch
Color	Black (RAL 9005)
Weight	31.5 lb / 14.3 kg
Dimension	17.4"(W) x 25.6"(D) x 1.73"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	FCC, CE, RoHS, TAA Compliant

Available Configurations

LCD monitor

- 17" 1280 by 1024 LCD screen

keyboard + Point Device

- Wired optical mouse
- Wireless optical mouse

Video Input

- VGA
- HDMI + Speaker + VGA
- BNC + S-Video + Speaker + VGA
- DVI-D + HDMI + Audio + Speaker + VGA
- 3G-SDI + Speaker + VGA

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

VGA/USB KVM switch

- 8 port VGA/USB KVM switch
- 16 port VGA/USB KVM switch
- N/A

VGA/USB cable

Specifications subject to change without notice.

- 6-feet VGA/USB KVM cable
- 10-feet VGA/USB KVM cable
- N/A

HDMI/USB KVM switch

- 8 port HDMI/USB KVM switch - NO KVM cable
- N/A

HDMI/USB cable

- HDMI-USB KVM cable, 6 feet
- N/A

Request a Quote or Learn More

Contact us at **info@acnodes.com** or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.