KDN9192

19" 1280 x 1024 rack LCD console with a 104-key keyboard with standard optical mouse and VGA video input in a 1U high 27.6" depth rackmount drawer.



- 19" rack LCD console drawer
- Supports 1280 x 1024 native resolution
- VGA video input
- 104-key keyboard with a true optical mouse
- Option for DVI-D, HDMI, BNC, or 3G-SDI input
- 27.6" (700mm) drawer design for standard racks
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V DC power input

Description

The KDN9192 is a 19" rack LCD console drawer supporting 1280 x 1024 native resolution, VGA video input, and a 104-key keyboard with a true optical mouse in a 1U high 27.6" depth rack drawer. The console features a 1U slim design with a front handle and 2-point lock and front OSD buttons, providing users with a convenient way to control device settings.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Monitor	Size: 19 inch Native Resolution: 1280 x 1024 Brightness (cd/m²): 250 Contrast Ratio (typ): 1000:1 Colors: 16.7 M Viewing Angle: 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.294 Display Area (mm): 376.32H x 270.33V Surface Treatment: Haze 25%, Hard-coating Surface Hardness: 3H Backlight: LED MTBF (hrs): 30,000
Keyboard & Optical Mouse	104-key keyboard integrated with wired optical mouse

Specifications subject to change without notice.

Video input	VGA video input
Integrated KVM (Option)	Integrated KVM switch is only available upon request Option for VGA KVM, DVI-D KVM, Cat6 KVM, or Matrix Cat6 KVM integration
Cable	1 x 6ft VGA USB console cable included
Mounting Distance	28 ~ 36.2 inch (710 ~ 920 mm)
Power supply	Input: Auto-sensing 100 to 240VAC, 50/60Hz Power Consumption: Max. 22W, Standby 2W Option for 12V / 24V / 48V / 125V DC power input
Color	Black (RAL 9005)
Weight	33.7 lb / 15.3 kg
Dimension	17.4"(W) x 27.6"(D) x 1.73"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	FCC, CE, RoHS, TAA Compliant

Available Configurations

LCD monitor

- 19" 1280 by 1024 LCD screen

keyboard + Point Device

- Wired optical mouse
- Wireless optical mouse

Video Input

- VGA
- DVI-D + HDMI + Audio + Speaker + VGA
- VGA + HDMI + Speaker
- BNC + S-Video + Speaker + VGA
- 3G-SDI + Speaker + VGA

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 125VDC power adapter

Specifications subject to change without notice.

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.