KDR-AV19

19" 1280 x 1024 multi-display rackmount console drawer with dual or triple displays, a 104-key keyboard with touchpad, VGA + DVI-D video input, and a 2U high rack enclosure.



- 2U multi-display rackmount display drawer
- Dual or triple 19" industrial LCD panels
- Supports 1280 x 1024 native resolution
- 104-key keyboard with touchpad
- VGA + DVI-D video input
- Option for HDMI 1.2 / HDCP 1.1 input (per panel)
- Built-in solid bearing slide rails & dual stereo speaker
- Auto-sensing 100 to 240VAC, 60/75 Hz power input
- Option for 12V / 24V / 48V DC power input

Description

The KDR-AV19 is a 2U multi-display console drawer featuring dual or triple 19" LCD monitors. The consoles support 1280 x 1024 native resolution, VGA + DVI-D video input, a 104-key keyboard with a 2-button touchpad, and 100/240VAC power input. Designed for small size and transit case portability, the KDR-AV19 is enclosed in a 2U high 22" depth enclosure with a firm and rigid handle design for easy access.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 19 inch Resolution: 1280 x 1024 Brightness (cd/m²): 250 Contrast Ratio (typ.): 1000:1 Display Area (mm): 337.92H x 270.33V Viewing Angle (L/R/U/D): 85/85/80/80 Response Time (ms): 5 Dot Pitch (mm): 0.294 Colors: 16.7M Surface Treatment: Haze 25%, Hard-coating Surface Hardness: 3H Backlight Type: LED MTBF (hrs): 30,000

Specifications subject to change without notice.

LCD Mounting Position	KDR-AV19-2L: Dual display (left hinged mount) KDR-AV19-2R: Dual display (right hinged mount) KDR-AV19-3: Triple display
KB & MS	104-key keyboard with touchpad pointing device Option for keyboard with trackball pointing device
Video Input	Standard: VGA + DVI-D Option: HDMI 1.2 /HDCP 1.1 input (per panel)
Front Panel Control	Power on/off switch OSD (on-screen display)
Drawer Design	Built-in solid bearing slide rails Mounting Distance: 21.7~31.1 inch (550~790 mm)
Power Supply	Input: Auto-sensing 100 to 240VAC, 50/60Hz Consumption Per Panel: Max. 22W, Saving Mode 2W Option for 12V / 24V / 48V DC power input
Color	Black
Weight	Dual Display: 48.4 lb / 22 kg Triple Display: 58.7 lb / 26.7 kg
Dimension	Product: 22.8"(W) x 23.6"(D) x 7.8"(H) Packing: 22.9"(W) x 29.7"(D) x 8.5"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.