PKD8175

All aluminum construction portable dumb terminal comes with three 17.3 inch 1920 x 1080 or 5760 x 1080 (Max.) full HD LCD panels, keyboard with touchpad, Display Port + mini DP + HDMI + DVI video input, and AC power supply.



- All aluminum construction portable dumb terminal
- Rugged aluminum housing with dual rail design & key lock mechanism
- Triple 17.3” 1920 x 1080P industrial LCD panel
- 5760 x 1080 full HD display resolutions
- Display Port / mini DP / HDMI / DVI video input
- Keyboard with touchpad (USB)
- Wide range 100V~240V AC power input

Description

Portable dumb terminal with triple 17.3 inch 1920 x 1080 (3) or 5760 x 1080 (Max.) full HD LCD panel, keyboard & touchpad, rugged aluminum chassis with heavy-duty shock-absorbing composite rubber corner blocks, Display Port + mini DP + HDMI + DVI video input, and 100~240V AC power supply.

Technical Specifications

SPECIFICATION	VALUE
Construction	Aluminum chassis and heavy-duty shock-absorbing composite rubber corner blocks
LCD panel	Size: 17.3” x 3 Resolution: 1920 x 1080 (3) or 5760 x 1080 (Max) Brightness: 300 cd/m^2 Contrast Ratio: 650:1 Response: 6ms Backlight: LED Colors: 262K
Video Input	Primary: Display Port Second / Third: HDMI / DVI / Display Port
Power Supply	Power adapter with 110/220V power input Option for DC 5V/12V power input
Keyboard and touch pad	keyboard and touch pad (USB)

Specifications subject to change without notice.

Weight	48lb
Dimension	17.32”(W) x 4.66”(H) x 11.41“(D)
Environmental	Operating Temperature: 0°C to 50°C Storage Temperature: -20°C to 50°C Humidity: 5~95%, non-condensing Altitude: 15,000 ft. Shock: 15g, 11ms Vibration: 20~60GHz, 0.075mm Drop: 3 ft. heights free drop
Safety:	FCC Class B, CE

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.