RMW6170

17.3" 1920 x 1080P Full HD rackmount LCD monitor with VGA + HDMI (no speaker) video input and 100/240VAC power input in an 8U high rackmount enclosure.



- 6U 17.3" FHD rackmount LCD monitor
- Supports 1920 x 1080 native resolution
- Front OSD (on-screen display) function
- VGA + HDMI (no speaker) video input
- Option for DVI-D, DP, Audio, Speaker, or 3G/HD/SD-SDI input
- Option for Resistive or Projected Capacitive touch screen - USB
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V DC power input

Description

The RMW6170 is a high-quality 6U 17.3" FHD rackmount LCD monitor designed to meet your display needs in any professional setting. Featuring a native resolution of 1920 x 1080, this monitor delivers crystal-clear images that are sure to impress. The front OSD (on-screen display) function allows you to easily adjust the settings to your preference, while the VGA + HDMI (no speaker) video input ensures compatibility with a wide range of devices. Additionally, the RMW6170 also offers the option for DVI-D, DP, Audio, Speaker, or 3G/HD/SD-SDI input, providing you with even more flexibility and versatility.

Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel
LCD panel	Size: 17.3 inch Max Resolution: 1920 x 1080 Brightness (cd/m²): 300 Contrast Ratio (typ.) : 1000:1 Colors: 16.7 M, 8-bit Viewing Angle (H/V): 178° x 178° Response Time (ms): 25 Dot Pitch (mm): 0.1989 Display Area (mm): 381.888H x 214.812V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight: LED

Specifications subject to change without notice.

	MTBF (hrs): 15,000
Video Input	Standard: VGA + HDMI (no speaker) video input Option: DVI-D, DP, Audio, Speaker, or 3G/HD/SD-SDI input
Touch screen (Option)	Resistive 1-pt touch screen - USB port Projected Capacitive 1-pt / 10-pt touch screen - USB
Front panel control	Power on/off switch OSD membrane switch
Connector	1 x VGA + 1 x HDMI (no speaker)
Power Supply	Input: Auto-sensing 100 to 240VAC, 50/ 60Hz Consumption: Max. 14 Watt, Standby 2 Watt Option for 12V / 24V / 48V / 125V DC power input
Mounting	6U high rackmount monitor for a standard 19" wide rackmount cabinet
Color	Black front panel (RAL 9005)
Weight	9.8 lb / 4.5 kg
Dimension	Product: 18.9"(W) x 1.9"(D) x 10.5"(H) Packing: 20.8"(W) x 4.9"(D) x 17.8"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11 ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA

Available Configurations

LCD monitor

- 17.3" 1920 by 1080 full HD LCD screen

Touch Screen

- N/A
- 17-Resistive touch screen, 1-pt USB port
- Projected Capacitive touch screen,10-pt USB port

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 125VDC power adapter

Video Input

- VGA + HDMI W/speaker
- MCS + VGA + HDMI (no speaker) + MCS (Multi-display control over serial port)

Specifications subject to change without notice.

- BNC + Audio IN + Speaker + VGA + HDMI
- DP + HDMI-1.4 + HDMI-1.4 + Audio + Speaker + VGA
- DVI-D + Audio + Speaker + VGA + HDMI
- 3G-SDI + VGA + HDMI + Speaker
- VGA + HDMI (No spaker)

IP65 / NEMA4 rated front bezel

- N/A
- IP65 / NEMA4 rated front bezel

Request a Quote or Learn More

Contact us at **info@acnodes.com** or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.