RMW6171

17.3" 4K 3840x2160 6U rackmount LCD monitor with DP-1.2 + HDMI-2.0 + HDMI-1.4 + Speaker video input and 100/240 VAC power input in an 6U high rackmount enclosure.



- 17.3" 4K 3840 x 2160 6U rackmount LCD monitor
- Supports 1920 x 1080 & 1600 x 1200/16.7M color (8-bit)
- Option for projected capacitive 10-pt / resistive1-pt
- Front OSD (on-screen display) function
- DP-1.2 + HDMI-2.0 + HDMI-1.4
- 2 x 2W stereo speaker
- Option for Resistive or Projected Capacitive touch screen - USB
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V / 250V DC power input

Description

The RMW6171 is a high-quality 17.3" 4K 3840x2160 6U rackmount LCD monitor designed to meet your display needs in any professional setting. Support 1920x1080 and 1600x1200 display resolution, this monitor delivers crystal-clear images that are sure to impress. The front OSD (on-screen display) function allows you to easily adjust the settings to your preference, while the DP-1.2 + HDMI-2.0 + HDMI-1.4 + Speaker video input ensures compatibility with a wide range of devices

Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel
LCD panel	Size: 17.3 inch 4K rackmount Max Resolution: 3840 x 2160 Brightness (cd/m²): 400 Contrast Ratio (typ.) : 1000:1 Colors: 16.7 M, 8-bit Viewing Angle (H/V): 178° x 178° Active Response Time (ms): 25 Dot Pitch (mm): 0.1989 Display Area (mm): 381.888H x 214.812V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight: LED

Specifications subject to change without notice.

	MTBF (hrs): 20,000
Video Input	Standard: DP-1.2 + HDMI-2.0 + HDMI-1.4 + Speaker
Touch screen (Option)	Projected Capacitive 10-pt / Resistive 1-pt - USB
Front panel control	Power on/off switch
Connector	1 x DP1.4 + 1 x HDMI 1.4 + 1 x HDMI 2.0
Power Supply	Input: Auto-sensing 100 to 240VAC, 50/ 60Hz Consumption: Max. 29 Watt, Standby 2 Watt Option for 12V / 24V / 48V / 125V / 250V DC power input
Mounting	6U high rackmount monitor for a standard 19" wide rackmount cabinet Black front panel
Color	Black front panel (RAL 9005)
Weight	9.2 lb/4.2 kg (net)/ 13.6 lb/6.2 kg (gross)
Dimension	Product: 18.9"(W) x 1.9"(D) x 10.5"(H) Packing: 20.8"(W) x 4.9"(D) x 17.8"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11 ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA

Available Configurations

LCD

- 17.3" 4K 3840 x 2160

Video ipunt

- 3G-SDI + DP-1.2 + HDMI-2.0 + HDMI-1.4 + Speaker
- DP-1.2 + HDMI-2.0 + HDMI-1.4 + Speaker

Touch screen

- Resistive touch screen, 1-pt
- Projected Capacitive touch screen,10-pt
- N/A

Power supply

- 12VDC
- 24VDC
- 48VDC
- 125VDC
- 110/220VAC

IP rated front bzel

Specifications subject to change without notice.

- IP65 rated front bezel
- N/A

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.