RMW7190

19" 1440 x 900 widescreen LCD monitor with VGA + HDMI (no speaker) video input, OSD membrane switch, and 100/240VAC power input in a 7U high rackmount enclosure.



- 7U 19" widescreen rackmount LCD monitor
- Supports 1440 x 900 native resolution
- VGA + HDMI (no speaker) video input
- Front OSD (on-screen display) function
- Option for DVI-D, BNC, Audio, Speaker, or 3G-SDI input
- Option for Resistive 1-pt touch screen - USB
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V DC power input

Description

The RMW7190 is a high-quality 7U 19" widescreen rackmount LCD monitor designed for professionals who require superior display quality in a variety of settings. With a native resolution of 1440 x 900, this monitor delivers clear and sharp images that are perfect for a wide range of applications. The RMW7190 supports VGA + HDMI (no speaker) video input and offers a range of input options, including DVI-D, BNC, Audio, Speaker, or 3G-SDI input, making it the perfect solution for use in professional broadcast environments. The RMW7190 is a reliable and robust rackmount LCD monitor that offers exceptional display quality, a wide range of input options, and compatibility with different power inputs. It is the perfect choice for professionals across various industries, including broadcast, industrial, military, and medical settings.

Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel
LCD panel	Size: 19 inch Max Resolution: 1440 x 900 Brightness (cd/m²): 250 Contrast Ratio (typ.) : 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.2835 Display Area (mm): 408.24H x 255.15V

Specifications subject to change without notice.

	Surface Treatment: Anti-glare Surface Hardness: 3H Backlight: LED MTBF (hrs): 30,000
Video input	Standard: VGA + HDMI (no speaker) video input Option: DVI-D, BNC, Audio, Speaker, or 3G-SDI input
Touch screen (Option)	Resistive 1-pt touch screen - USB
Connector	1 x VGA + 1 DVI-D
Front panel control	Power on/off switch OSD membrane switch
Power Supply	Input: Auto-sensing 100 to 240VAC, 50/60Hz Consumption: Max. 20 Watt, Standby 2 Watt Option for 12V / 24V / 48V / 125V DC power input
Mounting	7U high rackmount monitor for a standard 19" wide rackmount cabinet
Weight	12.8 lb / 5.8 kg
Dimension	Product: 18.9"(W) x 2.3"(D) x 12.2"(H) Packing: 20.8"(W) x 4.9"(D) x 17.8"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11 ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA

Available Configurations

LCD monitor

- 19" 1440 by 900 wide screen LCD monitor

Touch Screen

- N/A
- 19-inch wide screen resistive-type touch screen with USB port

Video Input

- VGA + HDMI (no speaker)
- VGA + HDMI + speaker
- DVI-D + Audio + Speaker + VGA + HDMI
- BNC + Audio IN + Speaker + VGA + HDMI
- VGA + HDMI (no speaker) +MCS (Multi-display control over serial)
- 3G-SDI + VGA + HDMI + Speaker

Power Supply

- 110/220VAC power supply
- 12VDC power adapter

Specifications subject to change without notice.

- 24VDC power adapter
- 48VDC power adapter
- 125VDC power adapter

IP65 / NEMA4 rated front bezel

- N/A
- IP65 / NEMA4 rated front bezel

Request a Quote or Learn More

Contact us at **info@acnodes.com** or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.